



## Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

 Creation Date:
 03/08/2018

 Datasheet No:
 DS105W

 Parker Part No:
 925582Q

 OEM:
 Pall

 OEM Part No:
 HC9020FKP4H&Z

 Product Dimensions

 A (mm)
 45.5
 (inch)
 1.79

B (mm)


D (mm)

E (mm)

25.8

45.5

112.5





Construction Materials	
Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Glass reinforced nylon or mil
Bottom Endcap:	Glass reinforced nylon or mil
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

(inch)

(inch)

(inch)

1.02

1.79

4.43

## **Calculated Performance Criteria**

 Differential Pressure (∆p):
 0.01 bar @ 10 l/min

 Tested to ISO3968 @ 32 cSt
 0.16 psi @ 2.20 gpm

Efficiency: >Beta 200 @ N/A microns & greater >Beta 1000 @ 4.5 microns & greater

Minimum Collapse Pressure: >20 bar Tested to ISO2941 >290 psi

## **Dirt Holding Capacity acc. to ISO16889**

>10.3 gram @ 7 bar terminal pressure drop >10.3 gram @ 102 psi terminal pressure drop

