



Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

 Creation Date:
 03/08/2018


 Datasheet No:
 DS669W

 Parker Part No:
 938271Q

 OEM:
 Hydac

 OEM Part No:
 0160R010BN4HC

Product Dimensions			
A (mm)	73.5	(inch)	2.89
C (mm)	34.5	(inch)	1.36
D (mm)	73.5	(inch)	2.89
E (mm)	144.0	(inch)	5.67
G (mm)	36.0	(inch)	1.42
H (mm)	13.5	(inch)	0.53





Construction Materials

Seal(s):	FPM: Fluoroelastomer	
Top Endcap:	Glass reinforced nylon	
Bottom Endcap:	Glass reinforced nylon	
Inner Support Cylinder:	Mild steel tin plated	
Filter Media:	Multilayer fibreglass with coated mesh on both sides	

Calculated Performance Criteria

Differential Pressure (Δp):0.41 bar @ 160 l/minTested to ISO3968 @ 32 cSt5.95 psi @ 35.20 gpm

Efficiency: >Beta 200 @ 10 microns & greater

>Beta 1000 @ 12 microns & greater

Minimum Collapse Pressure: >20 bar Tested to ISO2941 >290 psi

Dirt Holding Capacity acc. to ISO16889

12.8 gram @ 4 bar terminal pressure drop 12.8 gram @ 58 psi terminal pressure drop

