


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	03/08/2018
Datasheet No:	DS690W
Parker Part No:	938292Q
OEM:	Hydac
OEM Part No:	0660R020BN4HC

Product Dimensions

A (mm)	114.0	(inch)	4.49
C (mm)	68.5	(inch)	2.70
D (mm)	114	(inch)	4.49
E (mm)	333.0	(inch)	13.11
G (mm)	65.5	(inch)	2.58
H (mm)	18.5	(inch)	0.73



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Glass reinforced nylon
Bottom Endcap:	Glass reinforced nylon
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.31 bar @ 660 l/min
Tested to ISO3968 @ 32 cSt	4.50 psi @ 145.18 gp
Efficiency:	>Beta 200 @ 20 microns & greater >Beta 1000 @ 22 microns & greater
Minimum Collapse Pressure:	>20 bar
Tested to ISO2941	>290 psi
Dirt Holding Capacity acc. to ISO16889	52.4 gram @ 4 bar terminal pressure drop 52.4 gram @ 58 psi terminal pressure drop