


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	03/08/2018
Datasheet No:	DS1103W
Parker Part No:	938339Q
OEM:	MP Filtri
OEM Part No:	HP0653A10VN&AN

Product Dimensions

A (mm)	45.0	(inch)	1.77
B (mm)	25.5	(inch)	1.00
D (mm)	45	(inch)	1.77
E (mm)	209.0	(inch)	8.23



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.46 bar @ 150 l/min
Tested to ISO3968 @ 32 cSt	6.67 psi @ 33.00 gpm
Efficiency:	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
Minimum Collapse Pressure:	>20 bar
Tested to ISO2941	>290 psi
Dirt Holding Capacity acc. to ISO16889	>13.8 gram @ 7 bar terminal pressure drop >13.8 gram @ 102 psi terminal pressure drop