



Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date: 03/08/2018

Datasheet No: DS1560W

Parker Part No: 940359Q

OEM: Donaldson

P550786 **OEM Part No:**

Product Dimensions

D (mm)	95.0	(inch)	3.74
E (mm)	154.0	(inch)	6.06

1"-12 UNF 2B F





Construction Materials

Seal(s): NBR: Perbunan

Top Endcap: Mild steel zinc plated

Bottom Endcap: Mild steel zinc plated

Inner Support Cylinder: Mild steel tin plated

Steel Canister:

Aluminum **Top Plate:**

Filter Media: Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure ($\triangle p$): bar @ I/min psi @ gpm Tested to ISO3968 @ 32 cSt

Efficiency: >Beta 200 @ 20 microns & greater

>Beta 1000 @ 22 microns & greater

Minimum Collapse Pressure: >15 bar Tested to ISO2941 >218 psi

Dirt Holding Capacity acc. to ISO16889

36.8 gram @ bar terminal pressure drop 36.8 gram @ psi terminal pressure drop

Notes: By-pass setting: 2.5 bar



ENGINEERING YOUR SUCCESS.

www.parker.com/parfit