



Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date: 03/08/2018 **Datasheet No:** DS1320W Parker Part No: 940420Q OEM: Pall **OEM Part No:** UE319AP13Z **Product Dimensions** A (mm) 79.2 (inch) 3.12 D (mm) 79.2 (inch) 3.12 E (mm) 358 (inch) 14.09 2.48 G (mm) 62.9 (inch) H (mm) 12.7 0.50 (inch)

| Construction Materials | |
|------------------------|---|
| Seal(s): | FPM: Fluoroelastomer |
| Top Endcap: | Glass reinforced nylon |
| Bottom Endcap: | Glass reinforced nylon |
| Filter Media: | Multilayer Static Control fibreglass with coated mesh on both sides |

| Calculated Performance Criteria | | |
|---|--|--|
| Differential Pressure (△p): Tested to ISO3968 @ 32 cSt | 0.20 bar @ 100 l/min 2.90 psi @ 22.00 gpm | |
| Efficiency: >Beta 200 @ microns & greater >Beta 1000 @ 4.5 microns & greater | | |
| Minimum Collapse Pressure: Tested to ISO2941 | >10 bar >145 psi | |
| Dirt Holding Capacity acc. to ISO16889 84.0 gram @ 5 bar terminal pressure drop 84.0 gram @ 73 psi terminal pressure drop | | |

