


# Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

<b>Creation Date:</b>	03/08/2018
<b>Datasheet No:</b>	DS1077W
<b>Parker Part No:</b>	943615Q
<b>OEM:</b>	MP Filtri
<b>OEM Part No:</b>	HP0651A10VH&AH

**Product Dimensions**

<b>A (mm)</b>	45.0	<b>(inch)</b>	1.77
<b>B (mm)</b>	25.4	<b>(inch)</b>	1.00
<b>D (mm)</b>	45	<b>(inch)</b>	1.77
<b>E (mm)</b>	86.0	<b>(inch)</b>	3.39



**Construction Materials**

<b>Seal(s):</b>	FPM: Fluoroelastomer
<b>Top Endcap:</b>	Steel tin plated
<b>Bottom Endcap:</b>	Steel tin plated
<b>Inner Support Cylinder:</b>	Mild steel tin plated
<b>Filter Media:</b>	Multilayer fibreglass with coated mesh on the inflow side and stainless steel mesh on the outlet side

**Calculated Performance Criteria**

<b>Differential Pressure (<math>\Delta p</math>):</b>	0.37 bar @ 40 l/min
<b>Tested to ISO3968 @ 32 cSt</b>	5.37 psi @ 8.80 gpm
<b>Efficiency:</b>	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
<b>Minimum Collapse Pressure:</b>	>210 bar
<b>Tested to ISO2941</b>	>3046 psi
<b>Dirt Holding Capacity acc. to ISO16889</b>	>5.5 gram @ 7 bar terminal pressure drop >5.5 gram @ 102 psi terminal pressure drop