


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	03/08/2018
Datasheet No:	DS1061W
Parker Part No:	943647Q
OEM:	MP Filtri
OEM Part No:	HP3203A10VH&AH

Product Dimensions

A (mm)	78.0	(inch)	3.07
B (mm)	40.2	(inch)	1.58
D (mm)	78	(inch)	3.07
E (mm)	375.0	(inch)	14.76



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Steel tin plated
Bottom Endcap:	Steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on the inflow side and stainless steel mesh on the outlet side

Calculated Performance Criteria

Differential Pressure (Δp):	0.46 bar @ 600 l/min
Tested to ISO3968 @ 32 cSt	6.67 psi @ 131.98 gp
Efficiency:	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
Minimum Collapse Pressure:	>210 bar
Tested to ISO2941	>3046 psi
Dirt Holding Capacity acc. to ISO16889	>65.9 gram @ 7 bar terminal pressure drop >65.9 gram @ 102 psi terminal pressure drop