


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

| | |
|------------------------|-------------|
| Creation Date: | 03/08/2018 |
| Datasheet No: | DS1014W |
| Parker Part No: | 943820Q |
| OEM: | MP Filtri |
| OEM Part No: | CU630A25V&N |

Product Dimensions

| | | | |
|---------------|-------|---------------|------|
| A (mm) | 130.0 | (inch) | 5.12 |
| B (mm) | 76.0 | (inch) | 2.99 |
| C (mm) | 76 | (inch) | 2.99 |
| D (mm) | 130.0 | (inch) | 5.12 |
| E (mm) | 250.0 | (inch) | 9.84 |



Construction Materials

| | |
|--------------------------------|--|
| Seal(s): | FPM: Fluoroelastomer |
| Top Endcap: | Glass reinforced nylon |
| Bottom Endcap: | Glass reinforced nylon |
| Inner Support Cylinder: | Mild steel tin plated |
| Filter Media: | Multilayer fibreglass with coated mesh on both sides |

Calculated Performance Criteria

| | |
|---|---|
| Differential Pressure (Δp): | 0.44 bar @ 750 l/min |
| Tested to ISO3968 @ 32 cSt | 6.38 psi @ 164.98 gp |
| Efficiency: | >Beta 200 @ 20 microns & greater >Beta 1000 @ 22 microns & greater |
| Minimum Collapse Pressure: | >10 bar |
| Tested to ISO2941 | >145 psi |
| Dirt Holding Capacity acc. to ISO16889 | >42.1 gram @ 4 bar terminal pressure drop >42.1 gram @ 58 psi terminal pressure drop |