


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	03/08/2018
Datasheet No:	DS962W
Parker Part No:	944097Q
OEM:	Argo
OEM Part No:	V3.0723-08 (in to out)

Product Dimensions

A (mm)	63.7	(inch)	2.51
B (mm)	28.5	(inch)	1.12
D (mm)	63.7	(inch)	2.51
E (mm)	232.0	(inch)	9.13



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Outer Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.15 bar @ 80 l/min
Tested to ISO3968 @ 32 cSt	2.18 psi @ 17.60 gpm
Efficiency:	>Beta 200 @ 20 microns & greater >Beta 1000 @ 22 microns & greater
Minimum Collapse Pressure:	>10 bar
Tested to ISO2941	>145 psi
Dirt Holding Capacity acc. to ISO16889	29.9 gram @ 5 bar terminal pressure drop 29.9 gram @ 73 psi terminal pressure drop