

2749D-03V34 and 2749D-05V34

The new 3,000 bar technology



- Excellent Flexibility
- Smaller Outer Diameter
- Extremely Lightweight
- “State of the art” fitting technology
- Worldwide availability through specialised and authorised distributors
- **Certified**
acc. to DIN EN 1829-2



Contact:

**Parker Hannifin Manufacturing
Germany GmbH & Co. KG**
polyflex Division
An der Tuchbleiche 4
D – 68623 Lampertheim
Tel **06256 81-0**
Fax **06256 81-123**
polyflex@parker.com

www.parker.com/polyflex

Advantages:

- Breakthrough technology with the smallest outer diameter available in the market at **43,645 psi (301 MPa)** for both DN 5 and DN 8
- Less operator fatigue and more efficient handling due to an extremely lightweight hose
- The 2X fitting series can be used

	2749D-03V34		2749D-05V34	
Inner diameter	4.8 mm	0.189 in	7.8 mm	0.307 in
Outer diameter	13.3 mm	0.525 in	17.3 mm	0.681 in
Bend radius	200 mm	7.874 in	230 mm	9.055 in
Weight	0.47 kg/m	0.32 lb/ft	0.83 kg/m	0.56 lb/ft



ENGINEERING YOUR SUCCESS.