


XtreamSorb® PEACH® + CARBON BLOCK FILTER-ADSORBER CARTRIDGES

Series XS, XSG


for use in PECO Series 10, 14 & 55C (with adapter) vessels or competitor vessels of similar design



“REVOLUTIONIZE YOUR PROCESS PURIFICATION, UPGRADE CARBON CANISTERS WITH XTREAMSORB”

The XtreamSorb, Series XS and XSG, filter-adsorber cartridges incorporate both PEACH filtration technology and proprietary carbon block technology to provide an unprecedented two-stage cartridge with filtration and adsorption capabilities all in one. It removes the need for separate upstream particulate

filtration and provides maximized adsorption of impurities such as heavy hydrocarbons, degradation compounds and aromatics from process liquids and water. The block does not release carbon fines into the downstream effluent, which removes the need for separate downstream particulate filtration as well.



BEST OF BOTH WORLDS IN ONE SINGLE CARTRIDGE!

First stage PEACH media filters and captures solid particulate. This keeps the second stage carbon block pores free from solid contaminants maximizing adsorption of heavy hydrocarbons and aromatics.

1st Stage PEACH® Filter

- Most unique depth style filter cartridges on the market.
- Advanced solids removal of PEACH first stage protects downstream carbon block.
- PEACH's oleophilic nature attracts larger hydrocarbon droplets and semi-solids, decreasing loading on carbon block resulting in longer service life.

2nd Stage Carbon Block Adsorber

- Proprietary carbon block technology is specifically designed for removal of longer chain heavy hydrocarbons seen in TEG and Amine process purification systems.
- Carbon block's innovative structure prevents carbon movement and fluid channeling prevalent in traditional granular carbon.
- Carbon block yields a higher level of mass transfer kinetics, resulting in a smaller more ergonomic foot print and cleaner process stream.
- Eliminates the need for downstream particulate filtration.



ENGINEERING YOUR SUCCESS.

MATERIALS

FILTRATION MEDIA	Polyester or Polypropylene
ADSORPTION MEDIA	Proprietary carbon block technology
END CAPS	Polyester or Polypropylene
SEAL	Buna-N, EPDM, or Viton®

NOMINAL DIMENSIONS

SIZE	O.D.	I.D.	LENGTH
520	5.5"/139mm	2.2"/55mm	20" / 508mm
522	5.5"/139mm	2.2"/55mm	22" / 558mm
540	5.5"/139mm	2.2"/55mm	40" / 1016mm
544	5.5"/139mm	2.2"/55mm	44" / 1117mm

- Removal of heavy hydrocarbon impurities and aromatics from glycol and amine process liquids used to dehydrate and sweeten natural gas
- Removal of hydrocarbon color species from Natural Gas Liquids (NGL)
- Removal of hydrocarbons and aromatics from produced water streams

PERFORMANCE

EFFICIENCY: 99% of 10 micron
92% of 5 micron

OPERATING DATA


FLOW DIRECTION: Outside-to-Inside

MAX TEMP: Polypropylene: 180°F / 82°C
Polyester: 220°F / 104°C

MAX. DIFFERENTIAL PRESSURE: 20 psid / 1.3 bar

RECOMMENDED CHANGE-OUT DIFFERENTIAL PRESSURE: 10 psid / 0.68 bar

pH RANGE: Polypropylene: 3–13
Polyester: 3–10



Left: Rich Glycol before XstreamSorb
Right: Lean Glycol after one pass through XstreamSorb!

XS	—	544	—	V	—	CR 2.20	—	HC
SERIES		SIZE		SEAL		Cartridge fits both 2.20 & 1.56" risers		SERVICE
XS = Polypropylene Media & End Caps		520		CODE MATERIAL				CODE TYPE
XSG = Polyester Media & End Caps		522		B Buna-N				Blank Typical Process Applications
		540		E EPDM				HC Condensate Discoloration
		544		V Viton®				



**SCAN QR CODE FOR ADDITIONAL
PRODUCT INFORMATION INCLUDING
AVAILABLE PART NUMBERS**

For technical questions contact ipf.technical@support.parker.com or call 940-325-2575
To order, contact a support representative at ipf.support@support.parker.com or call 940-325-2575
Purchasing details: Request a quote at ipf.quotes@support.parker.com
Parker IPF Standard Terms & Conditions apply www.parker.com/IPF-Aftermarket-TOS

• Viton® is a registered trademarks of E. I. du Pont de Numours and Company.

© 2023 Parker Hannifin Corporation
DS-XSTREAMSORB-XS-231113

Parker Hannifin Corporation
Industrial Process Filtration Division
Phone 940-325-2575 | Toll Free 1-800-877-7326
www.parker.com/ipf

