



Data sheet

Quick connect coupling

Series 14

Coupling: 14KA	Plug: 22SF	DN: 5,5 = 25 mm ²
----------------	------------	------------------------------

Working pressure (static): 0 up to 35 bar

Working temperature: -20°C up to +100°C (depending on the seal material and medium)

Single shut off	<input checked="" type="checkbox"/>	Single hand operation	<input checked="" type="checkbox"/>	ULTRA-FLO-Valve	<input type="checkbox"/>
Double shut off	<input type="checkbox"/>	Two hand operation	<input type="checkbox"/>	Pipe-valve	<input type="checkbox"/>
Straight through	<input type="checkbox"/>	Ball locking system	<input type="checkbox"/>	U-Cup-Seal	<input type="checkbox"/>
Self venting	<input type="checkbox"/>	Pin locking system	<input checked="" type="checkbox"/>	O-Ring-Seal	<input checked="" type="checkbox"/>
Safety lock	<input type="checkbox"/>	Coupling anti-splash	<input checked="" type="checkbox"/>		<input type="checkbox"/>
Dry Break	<input type="checkbox"/>	Plug anti-splash	<input type="checkbox"/>		<input type="checkbox"/>

Materials:	Version	
	Standard	Nickel plated
Back body	Brass	Brass, nickel plated
Valve body	Brass	Brass, nickel plated
Sleeve	Brass	Brass, nickel plated
Valve	Brass	Brass
Spring	AISI 301	AISI 301
Locking Balls / Pins	AISI 420	AISI 420
Seals	Buna N	Buna N
Plug	Brass	Brass, nickel plated

Description:
 The 14 series (based on 26 series) is a rugged single-hand operated quick connect coupling made of brass. The interchangeability with ARO 210 allows a variety of applications. The advantages of 14 series are the robust construction of the coupling, single hand operated and multitude of connecting options. The 14 series can be used for many applications for example air tools, automotive, compressed air, mechanical engineering, compressors.

Interchangeability:
 ARO 210, PARKER 50, CEJN 300, ORION 44510, RECTUS 22 and various Swiss products

Versions / special equipment (in part not for all versions, others upon request):
 seal material Viton, Kalrez, Ethylen-Propylen;
 surface nickel plated, chrome plated, durnicoat;
 oil and grease free, silicon free;

Test values at 20°C (depending on the version):

Flow-rate air:	664 l/min at 6 bar inlet pressure and 0,5 bar pressure drop		
Flow-rate water:	9,1 l/min at 0,5 bar pressure drop		
Vacuum coupling:	min. 87 %	Weight coupling:	app. 98 g
Vacuum plug:	min. - %	Weight plug:	app. 31 g
Vacuum connected:	min. 87 %	Leakage rate / dead volume:	app. - ml
Connecting force:	w/o pressure app. 40 N	at 6 bar inlet pressure	app. 70 N
Disconnecting force:	w/o pressure app. 25 N	at 6 bar inlet pressure	app. 40 N
Safety factor:	at least 4-times	Burst-pressure:	at least 140 bar
Fatigue:	5000 cycles connecting/disconnecting tightness and function O.K.		

Revision	Date	Name		Date	Name	Document-no.: DB-14KA-SF-engl
			Made.	08.12.03	schwab	
			Check	08.12.03	schwab	
			Stand.			