



Data sheet

Quick connect coupling

Series 29

Coupling: 29KA

Plug: 29SF

DN: 13 = 130 mm²

Working pressure (static): 0 up to 35 bar

Working temperature: -20°C up to +100°C (depending on the seal material and medium)

Single shut off <input checked="" type="checkbox"/>	Single hand operation <input checked="" type="checkbox"/>	ULTRA-FLO-Valve <input checked="" type="checkbox"/>
Double shut off <input type="checkbox"/>	Two hand operation <input type="checkbox"/>	Pipe-valve <input type="checkbox"/>
Straight through <input type="checkbox"/>	Ball locking system <input checked="" type="checkbox"/>	U-Cup-Seal <input type="checkbox"/>
Self venting <input type="checkbox"/>	Pin locking system <input type="checkbox"/>	O-Ring-Seal <input checked="" type="checkbox"/>
Safety lock <input type="checkbox"/>	Coupling anti-splash <input checked="" type="checkbox"/>	<input type="checkbox"/>
Dry Break <input type="checkbox"/>	Plug anti-splash <input type="checkbox"/>	<input type="checkbox"/>

Materials:

Standard

Version

Back body	Steel, zinc plated	
Sleeve	Steel, hardened, zinc plated	
Valve	Brass	
Spring, Locking Ring	AISI 301	
Locking Balls	AISI 420	
Seals	Buna N	
Plug	Steel, hardened, zinc plated	

Description:

The 29KA series is an exceptional rugged steel coupling with single hand operation. The o-ring seal lies inside the plug front and is well protected against any external effects. Rough handling does not effect its sealing capability. Due to the ULTRA-FLO valve there is a very good flow performance. The 29KA series can be used for many applications for example air tools, compressed air, mining, building machinery, mechanical engineering.

Interchangeability:

-

Versions / special equipment (in part not for all versions, others upon request):

seal material Buna N, Viton, Kalrez, Ethylen-Propylen;
 surface nickel plated, chrome plated, durnicoat;
 oil and grease free, silicon free;

Test values at 20°C (depending on the version):

Flow-rate air:	2400 l/min at 6 bar inlet pressure and 0,5 bar pressure drop		
Flow-rate water:	36 l/min at 0,5 bar pressure drop		
Vacuum coupling:	min. 87 %	Weight coupling:	app. 385 g
Vacuum plug:	min. - %	Weight plug:	app. 165 g
Vacuum connected:	min. 87 %	Leakage rate / dead volume:	app. - ml
Connecting force:	w/o pressure app. 100 N	at 6 bar inlet pressure	app. 400 N
Disconnecting force:	w/o pressure app. 32 N	at 6 bar inlet pressure	app. 64 N
Safety factor:	at least 4-times	Burst-pressure:	at least 140 bar
Fatigue:	5000 cycles connecting/disconnecting tightness and function O.K.		

Revision	Date	Name		Date	Name	Document-no.: DB-29KA-SF-engl
			Made.	23.03.04	schwab	
			Check	23.03.04	schwab	
			Stand.			