



Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

 Creation Date:
 03/08/2018


 Datasheet No:
 DS798W

 Parker Part No:
 PR2843Q

 OEM:
 Mahle

 OEM Part No:
 Pi4208SMXVST25

Product Dimensions			
A (mm)	47.0	(inch)	1.85
B (mm)	25.5	(inch)	1.00
D (mm)	47	(inch)	1.85
E (mm)	171.0	(inch)	6.73





Top Endcap: Mild steel tin plated

Bottom Endcap: Mild steel tin plated

Inner Support Cylinder: Mild steel tin plated

Filter Media: Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (\Delta p): 0.48 bar @ 150 l/min **Tested to ISO3968 @ 32 cSt** 6.96 psi @ 33.00 gpm

Efficiency: >Beta 200 @ 20 microns & greater >Beta 1000 @ 22 microns & greater

......

Minimum Collapse Pressure: >210 bar Tested to ISO2941 >3046 psi

Dirt Holding Capacity acc. to ISO16889

13.3 gram @ 7 bar terminal pressure drop 13.3 gram @ 102 psi terminal pressure drop

