


## Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

<b>Creation Date:</b>	03/08/2018
<b>Datasheet No:</b>	DS789W
<b>Parker Part No:</b>	PR2874Q
<b>OEM:</b>	Mahle
<b>OEM Part No:</b>	Pi3245SMXVST10

### Product Dimensions

<b>A (mm)</b>	83.5	<b>(inch)</b>	3.29
<b>B (mm)</b>	47.5	<b>(inch)</b>	1.87
<b>D (mm)</b>	83.5	<b>(inch)</b>	3.29
<b>E (mm)</b>	372.0	<b>(inch)</b>	14.65



### Construction Materials

<b>Top Endcap:</b>	Mild steel tin plated
<b>Bottom Endcap:</b>	Mild steel tin plated
<b>Inner Support Cylinder:</b>	Mild steel tin plated
<b>Filter Media:</b>	Multilayer fibreglass with coated mesh on the inflow side and stainless steel mesh on the outlet side

### Calculated Performance Criteria

<b>Differential Pressure (<math>\Delta p</math>):</b>	0.35 bar @ 500 l/min
<b>Tested to ISO3968 @ 32 cSt</b>	5.08 psi @ 109.98 gp
<b>Efficiency:</b>	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
<b>Minimum Collapse Pressure:</b>	>210 bar
<b>Tested to ISO2941</b>	>3046 psi
<b>Dirt Holding Capacity acc. to ISO16889</b>	72.3 gram @ 7 bar terminal pressure drop 72.3 gram @ 102 psi terminal pressure drop