


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

| | |
|------------------------|---------------|
| Creation Date: | 03/08/2018 |
| Datasheet No: | DS518W |
| Parker Part No: | PR3057Q |
| OEM: | Hydac |
| OEM Part No: | 0060D005BN3HC |

Product Dimensions

| | | | |
|---------------|------|---------------|------|
| A (mm) | 47.0 | (inch) | 1.85 |
| B (mm) | 22.2 | (inch) | 0.87 |
| D (mm) | 47 | (inch) | 1.85 |
| E (mm) | 83.0 | (inch) | 3.27 |



Construction Materials

| | |
|--------------------------------|--|
| Seal(s): | FPM: Fluoroelastomer |
| Top Endcap: | Mild steel tin plated |
| Bottom Endcap: | Mild steel tin plated |
| Inner Support Cylinder: | Mild steel tin plated |
| Filter Media: | Multilayer fibreglass with coated mesh on both sides |

Calculated Performance Criteria

| | |
|---|--|
| Differential Pressure (Δp): | 0.77 bar @ 50 l/min |
| Tested to ISO3968 @ 32 cSt | 11.17 psi @ 11.00 gp |
| Efficiency: | >Beta 200 @ 6 microns & greater >Beta 1000 @ 7 microns & greater |
| Minimum Collapse Pressure: | >20 bar |
| Tested to ISO2941 | >290 psi |
| Dirt Holding Capacity acc. to ISO16889 | >7.5 gram @ 7 bar terminal pressure drop >7.5 gram @ 102 psi terminal pressure drop |