


# Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

<b>Creation Date:</b>	03/08/2018
<b>Datasheet No:</b>	DS907W
<b>Parker Part No:</b>	PR4503Q
<b>OEM:</b>	Mahle
<b>OEM Part No:</b>	Pi23016RNSMX10

### Product Dimensions

<b>A (mm)</b>	99.0	<b>(inch)</b>	3.90
<b>B (mm)</b>	52.8	<b>(inch)</b>	2.08
<b>C (mm)</b>	52.8	<b>(inch)</b>	2.08
<b>D (mm)</b>	99.0	<b>(inch)</b>	3.90
<b>E (mm)</b>	159.0	<b>(inch)</b>	6.26



### Construction Materials

<b>Seal(s):</b>	FPM: Fluoroelastomer
<b>Top Endcap:</b>	Mild steel tin plated
<b>Bottom Endcap:</b>	Mild steel tin plated
<b>Inner Support Cylinder:</b>	Mild steel tin plated
<b>Filter Media:</b>	Multilayer fibreglass with coated mesh on both sides

### Calculated Performance Criteria

<b>Differential Pressure (<math>\Delta p</math>):</b>	0.71 bar @ 100 l/min
<b>Tested to ISO3968 @ 32 cSt</b>	10.30 psi @ 22.00 gp
<b>Efficiency:</b>	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
<b>Minimum Collapse Pressure:</b>	>10 bar
<b>Tested to ISO2941</b>	>145 psi
<b>Dirt Holding Capacity acc. to ISO16889</b>	27.8 gram @ 4 bar terminal pressure drop 27.8 gram @ 58 psi terminal pressure drop