


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	03/08/2018
Datasheet No:	DS778W
Parker Part No:	PR4515Q
OEM:	Mahle
OEM Part No:	Pi25063RNSMX25

Product Dimensions

A (mm)	134.0	(inch)	5.28
B (mm)	70.5	(inch)	2.78
C (mm)	70.5	(inch)	2.78
D (mm)	134.0	(inch)	5.28
E (mm)	400.0	(inch)	15.75



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.34 bar @ 1400 l/min
Tested to ISO3968 @ 32 cSt	4.93 psi @ 307.96 gp
Efficiency:	>Beta 200 @ 20 microns & greater >Beta 1000 @ 22 microns & greater
Minimum Collapse Pressure:	>10 bar
Tested to ISO2941	>145 psi
Dirt Holding Capacity acc. to ISO16889	101.1 gram @ 4 bar terminal pressure drop 101.1 gram @ 58 psi terminal pressure drop