

A close-up, grayscale photograph of a Parker GlobalCore hose and fitting system. The hose is the central focus, with several fittings attached. The Parker logo and 'GLOBALCORE' are visible on the hose. The background is dark and out of focus, showing more of the system.

ANY PRESSURE.  
ANY PROJECT.  
**ONE SOLUTION.**

## GLOBALCORE™

The world's first high-performance,  
cohesive hose and fitting system.



ENGINEERING **YOUR** SUCCESS.

# PROVEN PERFORMANCE. GLOBAL SOLUTION.



Providing one simple solution of robust hydraulic hoses designed to endure the tough conditions where work gets done, **GlobalCore** is the future that OEMs and end users around the world have been asking for.



### HIGH PERFORMANCE

With GlobalCore hoses tested to twice their ISO 18752 standard, high performance in rugged environments and high impulse applications is ensured.



### COHESIVE

GlobalCore is a unified system that delivers hoses designed, engineered, and manufactured to the global specification, ISO 18752, which is based on performance and pressure requirements.



### GLOBAL

GlobalCore hoses are manufactured in major regions of the world, supporting the equipment they serve, regardless of where it was originally manufactured, or where it is today.



### SIMPLE

Select the GlobalCore hose based on the working pressure required for your application and one of two fitting series in a wide array of configurations.




For the latest list of hose and agency approvals, visit [parkerglobalcore.com](http://parkerglobalcore.com).



# 187 HOSE

## MEETING THE DEMANDS OF COMPLEX HYDRAULIC SYSTEMS AND HIGH PRESSURE RETURN LINES

Designed, build and tested to the ISO 18752 performance specifications. For high pressure return line applications in all markets.



Part Number	Cover Type			Hose I.D.				Hose O.D. mm	Pressure Rating				Vacuum* kPa	min. bend radius mm	weight kg
	Standard Cover 187	Tough Cover 187TC	Super Tough 187ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure				
	ISO 18752 Performance								MPa	psi	MPa	psi			
187XX-8	AC	AC	AC	12	1/2	-8	12.7	21.0	7.0	1000	28.0	4000	80	65	0.43
187XX-10	AC	AC	AC	16	5/8	-10	15.9	24.0	7.0	1000	28.0	4000	80	75	0.49
187XX-12	AC	AC	AC	19	3/4	-12	19.1	27.0	7.0	1000	28.0	4000	80	90	0.63
187XX-16	AC	AC	AC	25	1	-16	25.4	36.0	7.0	1000	28.0	4000	80	114	0.91
187XX-20	AC	AC	AC	31	1 1/4	-20	31.8	44.0	7.0	1000	28.0	4000	60	140	1.85
187XX-24	AC	AC	AC	38	1 1/2	-24	38.1	52.0	7.0	1000	28.0	4000	60	248	1.96
187XX-32	AC	AC	AC	51	1	-32	50.8	65.0	7.0	1000	28.0	4000	60	318	2.60
187XX-40	AS	AS	AS	63	2 1/2	-40	63.5	75.0	7.0	1000	28.0	4000	60	508	3.04
187XX-48	AS	AS	AS	76	3	-48	76.2	91.0	7.0	1000	28.0	4000	60	508	4.12

**Inner Tube:** Synthetic Rubber

**Reinforcement:** One- or two-braid steel wire

**Temperature Range:** Standard Cover: -40°C to +100°C,  
ToughCover & SuperTough: -40°C to +125°C  
For -40 & -48 sizes only -40°C to +100°C

**Fitting Series:**

Series 43/48 for sizes -8 to -32

Series 48 2piece for sizes -40 to -48



# 387 HOSE

## DELIVERING VALUE AND PERFORMANCE FOR HIGH-PRESSURE APPLICATIONS

Lightweight and flexible, 387 Hose consistently delivers maximum performance and hose life across all sizes and markets using an efficient force-to-flex design.



Part Number	Cover Type			Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	Standard Cover 387	Tough Cover 387TC	Super Tough 387ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure			
	ISO 18752 Performance								MPa	psi	MPa	psi		
387XX-4	AC	AC	AC	6	1/4	-4	6.4	13.4	21.0	3000	84.0	12000	50	0.24
387XX-6	AC	AC	AC	10	3/8	-6	9.5	17.4	21.0	3000	84.0	12000	65	0.34
387XX-8	AC	AC	AC	12	1/2	-8	12.7	20.7	21.0	3000	84.0	12000	90	0.43
387XX-10	AC	AC	AC	16	5/8	-10	15.9	23.9	21.0	3000	84.0	12000	100	0.49
387XX-12	AC	AC	AC	19	3/4	-12	19.1	27.8	21.0	3000	84.0	12000	120	0.86
387XX-16	AC	AC	AC	25	1	-16	25.4	35.4	21.0	3000	84.0	12000	150	1.17
387XX-20	BC	CC	CC	31	1 1/4	-20	31.8	46.3	21.0	3000	84.0	12000	210	2.59
387XX-24	BC	CC	CC	38	1 1/2	-24	38.1	52.8	21.0	3000	84.0	12000	250	2.99
387XX-32	BC	CC	CC	51	2	-32	50.8	66.2	21.0	3000	84.0	12000	320	4.09

**Inner Tube:** Synthetic Rubber

**Reinforcement:** One- or two-braid steel wire for sizes -4 to -16  
Four-spiral for sizes -20 to -32


**Temperature Range:** Standard Cover: -40°C to +100°C  
ToughCover & SuperTough: -40°C to +125°C

**Fitting Series:**

Series 43/48 for sizes -4 to -16

Series 43/77 for size -20

Series 77 for sizes -24 to -32



# 487 HOSE

## HIGHLY FLEXIBLE ACROSS ALL SIZES

Constructed for high performance and easy handling with low force-to-flex for ease of installation, 487 Hose excels in multiple applications around the world.



Part Number	ISO 18752 Performance			Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	Standard Cover 487	Tough Cover 487TC	Super Tough 487ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure			
	MPa	psi	MPa	psi	MPa	psi	MPa	psi						
487XX-4	AC	AC	AC	6	1/4	-4	6.4	13.1	28.0	4000	112.0	16000	50	0.30
487XX-6	AC	AC	AC	10	3/8	-6	9.5	17.2	28.0	4000	112.0	16000	65	0.42
487XX-8	AC	AC	AC	12	1/2	-8	12.7	20.4	28.0	4000	112.0	16000	90	0.52
487XX-10	AC	AC	AC	16	5/8	-10	15.9	23.9	28.0	4000	112.0	16000	100	0.66
487XX-12	AC	AC	AC	19	3/4	-12	19.1	27.8	28.0	4000	112.0	16000	120	0.86
487XX-16	BC	CC	CC	25	1	-16	25.4	37.8	28.0	4000	112.0	16000	150	1.99
487XX-20	BC	CC	CC	31	1 1/4	-20	31.8	46.3	28.0	4000	112.0	16000	210	2.59
487XX-24	BC	CC	CC	38	1 1/2	-24	38.1	52.8	28.0	4000	112.0	16000	250	3.08
487XX-32	BC	CC	-	51	2	-32	50.8	64.8	28.0	4000	112.0	16000	320	4.09

**Inner Tube:** Synthetic Rubber

**Reinforcement:** One- or two-braid steel wire for sizes -4 to -12

Four-spiral wires for sizes -16 to -24 | Six-spiral wires for size -32

**Temperature Range:** Standard Cover: -40°C to +100°C


ToughCover & SuperTough: -40°C to +125°C

**Fitting Series:**

Series 43/48 for sizes -4 to -12

Series 43 for size -16


Series 77 for sizes -20 to -32



# 722 HOSE

## RESILIENT 4-WIRE SPIRAL CONSTRUCTION

Engineered to ensure longer life in high-impulse, heavy-duty cycle applications, 722 Hose delivers maximum performance and efficiency.



Part Number	ISO 18752 Performance			Hose I.D.				Hose O.D. mm	Pressure Rating				min. bend radius mm	weight kg
	Standard Cover 722	Tough Cover 722TC	Super Tough 722ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure			
	MPa	psi	MPa	psi	MPa	psi	MPa	psi						
722XX-6	BC	CC	CC	10	3/8	-6	9.5	19.9	28.0	4000	112.0	16000	65	0.60
722XX-8	BC	CC	CC	12	1/2	-8	12.7	22.7	28.0	4000	112.0	16000	90	0.80
722XX-10	BC	CC	CC	16	5/8	-10	15.9	26.4	28.0	4000	112.0	16000	100	1.10
722XX-12	BC	CC	CC	19	3/4	-12	19.1	30.7	28.0	4000	112.0	16000	120	1.40
722XX-16	BC	CC	CC	25	1	-16	25.4	37.8	28.0	4000	112.0	16000	150	1.99

**Inner Tube:** Synthetic Rubber

**Reinforcement:** Four-spiral steel wire

**Temperature Range:** Standard Cover: -40°C to +100°C

ToughCover & SuperTough: -40°C to +125°C

**Fitting Series:**

Series 43



# 787 HOSE

## LIGHTER WEIGHT, HIGHER FLEXIBILITY, TIGHTER BEND RADIUS

With a Compact Spiral design that offers enhanced chemical compatibility in routing and installation, 787 Hose delivers superior performance in a lightweight, force-to-flex product.



Part Number	ISO 18752 Performance			Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
	Standard Cover 787	Tough Cover 787TC	Super Tough 787ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure			
								MPa	psi	MPa	psi	mm	kg	
787XX-4	AC	AC	AC	6	1/4	-4	6.3	13.0	35.0	5000	140.0	20000	50	0.31
787XX-6	AC	AC	AC	10	3/8	-6	10.0	17.2	35.0	5000	140.0	20000	63	0.42
787XX-8	BC	DC	DC	12	1/2	-8	12.7	21.1	35.0	5000	140.0	20000	90	0.67
787XX-10	BC	DC	DC	16	5/8	-10	15.9	23.9	35.0	5000	140.0	20000	100	0.80
787XX-12	BC	DC	DC	19	3/4	-12	19.1	27.9	35.0	5000	140.0	20000	120	1.16
787XX-16	BC	DC	DC	25	1	-16	25.4	35.7	35.0	5000	140.0	20000	150	1.74
787XX-20	BC	DC	DC	31	1 1/4	-20	31.8	44.9	35.0	5000	140.0	20000	210	2.89
787XX-24	BC	DC	DC	38	1 1/2	-24	38.1	52.8	35.0	5000	140.0	20000	255	3.96
787XX-32	BC	DC	DC	51	2	-32	50.8	67.6	35.0	5000	140.0	20000	318	6.50

**Inner Tube:** Synthetic Rubber

**Reinforcement:** Two-braid steel wire for sizes -4 to -6  
Four- or six-compact spiral steel wires for sizes -8 to -32

**Temperature Range:** Standard Cover: -40°C to +100°C  
ToughCover & SuperTough: -40°C to +125°C (-4 to -6 rated to +100°C)

**Fitting Series:**

Series 43/48 for sizes -4 and -6

Series 77 for sizes -8 to -32



35 MPa (5000 psi)

# 797 HOSE

## COMPACT DESIGN FOR TIGHTER ROUTING AND SPACE SAVINGS

Tested up to 2,000,000 cycles, 797 Hose provides enhanced chemical compatibility and service life with an easy-to-install compact spiral construction for high pressure, high impulse applications.



Part Number	ISO 18752 Performance			Hose I.D.				Hose O.D.	Pressure Rating				min. bend radius	weight
	Standard Cover 797	Tough Cover 797TC	Super Tough 797ST	DN	Inch	Size	mm		max. working pressure		min. burst pressure			
								MPa	psi	MPa	psi	mm	kg	
797XX-4	AC	AC	AC	6	1/4	-4	6.3	13.0	42.0	6000	168.0	24000	50	0.31
797XX-6	BC	CC	CC	10	3/8	-6	10.0	17.0	42.0	6000	168.0	24000	63	0.46
797XX-8	BC	DC	DC	12	1/2	-8	12.7	21.1	42.0	6000	168.0	24000	100	0.67
797XX-10	BC	DC	DC	16	5/8	-10	15.9	23.9	42.0	6000	168.0	24000	115	0.80
797XX-12	BC	DC	DC	19	3/4	-12	19.1	27.9	42.0	6000	168.0	24000	135	1.16
797XX-16	BC	DC	DC	25	1	-16	25.4	35.7	42.0	6000	168.0	24000	165	1.74
797XX-20	BC	DC	DC	31	1 1/4	-20	31.8	44.9	42.0	6000	168.0	24000	225	2.89
797XX-24	BC	CC	CC	38	1 1/2	-24	38.1	52.8	42.0	6000	168.0	24000	305	3.96
797XX-32	BC	CC	CC	51	2	-32	50.8	67.6	42.0	6000	168.0	24000	380	6.50

**Inner Tube:** Synthetic Rubber

**Reinforcement:** Two-braid steel wire for size -4  
Four- or six-compact spiral steel wires for sizes -6 to -32


**Temperature Range:** Standard Cover: -40°C to +100°C  
ToughCover & SuperTough: -40°C to +125°C (-4 rated to +100°C)

**Fitting Series:**

Series 43/48 for sizes -4

Series 43 for size -6

Series 77 for sizes -8 to -32



42 MPa (6000 psi)

# Parker Worldwide

## Europe, Middle East, Africa

**AE – United Arab Emirates,**  
Dubai

Tel: +971 4 8127100  
parker.me@parker.com

**AT – Austria,** St. Florian

Tel: +43 (0)7224 66201  
parker.austria@parker.com

**AZ – Azerbaijan,** Baku

Tel: +994 50 2233 458  
parker.azerbaijan@parker.com

**BE/NL/LU – Benelux,**

Hendrik Ido Ambacht  
Tel: +31 (0)541 585 000  
parker.nl@parker.com

**BG – Bulgaria,** Sofia

Tel: +359 2 980 1344  
parker.bulgaria@parker.com

**BY – Belarus,** Minsk

Tel: +48 (0)22 573 24 00  
parker.poland@parker.com

**CH – Switzerland,** Etoy

Tel: +41 (0)21 821 87 00  
parker.switzerland@parker.com

**CZ – Czech Republic,** Klecany

Tel: +420 284 083 111  
parker.czechrepublic@parker.com

**DE – Germany,** Kaarst

Tel: +49 (0)2131 4016 0  
parker.germany@parker.com

**DK – Denmark,** Ballerup

Tel: +45 43 56 04 00  
parker.denmark@parker.com

**ES – Spain,** Madrid

Tel: +34 902 330 001  
parker.spain@parker.com

**FI – Finland,** Vantaa

Tel: +358 (0)20 753 2500  
parker.finland@parker.com

**FR – France,** Contamine s/Arve

Tel: +33 (0)4 50 25 80 25  
parker.france@parker.com

**GR – Greece,** Piraeus

Tel: +30 210 933 6450  
parker.greece@parker.com

**HU – Hungary,** Budaörs

Tel: +36 23 885 470  
parker.hungary@parker.com

**IE – Ireland,** Dublin

Tel: +353 (0)1 466 6370  
parker.ireland@parker.com

**IL – Israel**

Tel: +39 02 45 19 21  
parker.israel@parker.com

**IT – Italy,** Corsico (MI)

Tel: +39 02 45 19 21  
parker.italy@parker.com

**KZ – Kazakhstan,** Almaty

Tel: +7 7273 561 000  
parker.easteurope@parker.com

**NO – Norway,** Asker

Tel: +47 66 75 34 00  
parker.norway@parker.com

**PL – Poland,** Warsaw

Tel: +48 (0)22 573 24 00  
parker.poland@parker.com

**PT – Portugal**

Tel: +351 22 999 7360  
parker.portugal@parker.com

**RO – Romania,** Bucharest

Tel: +40 21 252 1382  
parker.romania@parker.com

**RU – Russia,** Moscow

Tel: +7 495 645-2156  
parker.russia@parker.com

**SE – Sweden,** Spånga

Tel: +46 (0)8 59 79 50 00  
parker.sweden@parker.com

**SK – Slovakia,** Banská Bystrica

Tel: +421 484 162 252  
parker.slovakia@parker.com

**SL – Slovenia,** Novo Mesto

Tel: +386 7 337 6650  
parker.slovenia@parker.com

**TR – Turkey,** Istanbul

Tel: +90 216 4997081  
parker.turkey@parker.com

**UA – Ukraine,** Kiev

Tel: +48 (0)22 573 24 00  
parker.poland@parker.com

**UK – United Kingdom,** Warwick

Tel: +44 (0)1926 317 878  
parker.uk@parker.com

**ZA – South Africa,** Kempton Park

Tel: +27 (0)11 961 0700  
parker.southafrica@parker.com

## North America

**CA – Canada,** Milton, Ontario

Tel: +1 905 693 3000

**US – USA,** Cleveland

Tel: +1 216 896 3000

## Asia Pacific

**AU – Australia,** Castle Hill

Tel: +61 (0)2-9634 7777

**CN – China,** Shanghai

Tel: +86 21 2899 5000

**HK – Hong Kong**

Tel: +852 2428 8008

**IN – India,** Mumbai

Tel: +91 22 6513 7081-85

**JP – Japan,** Tokyo

Tel: +81 (0)3 6408 3901

**KR – South Korea,** Seoul

Tel: +82 2 559 0400

**MY – Malaysia,** Shah Alam

Tel: +60 3 7849 0800

**NZ – New Zealand,** Mt Wellington

Tel: +64 9 574 1744

**SG – Singapore**

Tel: +65 6887 6300

**TH – Thailand,** Bangkok

Tel: +662 186 7000

**TW – Taiwan,** Taipei

Tel: +886 2 2298 8987

## South America

**AR – Argentina,** Buenos Aires

Tel: +54 3327 44 4129

**BR – Brazil,** Sao Jose dos Campos

Tel: +55 800 727 5374

**CL – Chile,** Santiago

Tel: +56 2 623 1216

**MX – Mexico,** Toluca

Tel: +52 72 2275 4200

### EMEA Product Information Centre

Free phone: 00 800 27 27 5374

(from AT, BE, CH, CZ, DE, DK, EE, ES, FI, FR, IE, IL,  
IS, IT, LU, MT, NL, NO, PL, PT, RU, SE, SK, UK, ZA)

### US Product Information Centre

Toll-free number: 1-800-27 27 537

www.parker.com

