

Military Solutions

Parflex - Fluoropolymer Tubing Products



Fluoropolymer Tubing

For Military Applications

From the last frontier into the depths of the sea, Parker Hannifin Fluoropolymer Tubing products keep the military moving. Whether its the smallest piece of tubing, a standard heat shrinkable tube or an extra flexible convoluted tube, the fluoropolymer product line delivers virgin tubing that performs in extreme high or low temperatures.

Parker is 100% committed to supporting our military. Fluoropolymer tubing is produced at the Parflex Fort Worth facility under the Texloc brand. It is tested and certified to some of the most rigorous specifications in the industry.



- Compliant to Mil-Spec Certifications
- FDA Compliant
- Minimal longitudinal growth/shrinkage
- · Unlimited shelf life
- Salt water resistant
- Complete Traceability, Lot #, DOM
- · Value added services include:
 - -Cuffing
 - -Custom bellows
 - -Custom sizes
 - -Cut to length parts
 - -Drilled tubing
 - -Etched PTFE
 - -Formed tubing for quick installation
- -Jacketing
- -Tube flanging
- -Tube flaring
- -Tube forming
- -Tube slitting
- -Wire reinforcement
- of convoluted tubing



















Tubing Features:

- PTFE Tubing Temperature Range up to 500°F Lowest coefficient of friction
- Temperature Range up to 400°F Exceptional clarity, long continuous lengths
- ETFE Tubing Temperature Range up to 302°F Increased abrasion resistance

Applications:

- Bundling
- Split Loom
- Harnesses
- · Track Lighting Protection
- Electrical Insulation Beverage Lines
- Robotics





Typical Image	Specification*	Material	Product Description & Sizes
N.	AS23053/11, Class 1	FEP	Sizes 3/8" to 1-1/2"; AWG 24 - AWG 0
	AS23053/11, Class 2	FEP	Sizes 3/32" to 2"
Heatshrink	AS23053/12, Class 1	PTFE	Sizes 1/8" to 1"
	AS23053/12, Class 2	PTFE	Sizes 1/8" to 1"; AWG 24 - AWG 0
	AS23053/12, Class 3	PTFE	Sizes 1/8" to 1"; AWG 24 - AWG 0
	AS23053/12, Class 5	PTFE	Sizes 5/64" to 1-1/4"




*Products are dimensionally compliant to specifications; May not be exact equivalents






Convoluted	AS81914/1	PTFE	Convoluted, Standard Convolution, 81914/1 Sizes 3/16" to 2" I.D. Natural or Black	
	AS81914/2	PTFE	Convoluted, Close Convolution, 81914/2 Sizes 3/16" to 2" I.D. Natural or Black	
	AS81914/3	FEP	Convoluted, Standard Convolution, 81914/3 Sizes 3/16" to 2" I.D. Natural	
	AS81914/4	FEP	Convoluted, Close Convolution, 81914/4 Sizes 3/16" to 2" I.D. Natural	
	AS81914/5	ETFE	Convoluted, Close Convolution, 81914/5 Sizes 3/16" to 2" I.D. Natural	
	AS81914/6	ETFE	Convoluted, Standard Convolution, 81914/6 Sizes 3/16" to 2" I.D. Natural	
Visit the webpage			*Products are dimensionally compliant to specifications; May not be exact equivalents	











	FEP	ASTM D3296-03	
	TEI AOIM DO230-00		
Corrugated	TON.		
	Size	s 1/4" to 2-1/2" I.D.	

Visit the webpage

For technical information on these products, download Catalog 4660 at www.parker.com/pfd

^{*}Products are dimensionally compliant to specifications; May not be exact equivalents



© 2013-2023 Parker Hannifin Corporation - All Rights Reserved

Parker Hannifin Corporation
Parflex Division
1300 North Freedom St.
Ravenna, OH 44266
phone 330 296 2871
fax 330 296 8433
www.parker.com/parflex

Bul. 4660-4150-Military 8/23