

2. ALTERNATE DIMENSIONS IN BRACKETS IN INCHES. 3. CDAS HL050 PNEUMATIC ATEX SHOWN IN DRAWING.

D

ECO No. 0304038	RE	VВ
PLEASE CONSIDER THE ENVIRONMENT		
DO NOT SCALE - 1		
BASED ON BS 8888	DIMENSIONS IN MILL	IMETRES
GENERAL TOLERANCES UNLESS O	THERWISE STATED	
MACHINED DIMENSIONS		
.XX ±0.13 UP TO 30 .X ±0.25 OVER 300	0 ±0.3) TO 600 ±0.5	
POSITIONAL TOLERANCE		
PLAIN HOLES Ø0.13 TAPPED HOLES Ø0.26		
CONCENTRICITY TOLERANCE MACHINED SURFACES INDICATED		
SURFACE TEXTURE TO BS 1134	THUS	
VALUES IN MICROMETRES ANGLES ±1/2° (EXCEPT CHAMFER	25)	
METRIC THREADS TO BS 3643 ME	,	
EXTERNAL 6g INTERNAL 6H PIPE THREADS		
PRESSURE TIGHT TO BS 21		
SHEET METALWORK & FABRICATI SHEET METALWORK DIMENSIONS	DNS	
UP TO 500 ±0.5 OVER 500 TO 1000 ±1.0		
OVER 1000 ±1.5		
FABRICATED PARTS DIMENSIONS UP TO 500 ±2		
OVER 500 TO 1000 ±4 OVER 1000 ±6		
POSITIONAL TOLERANCE FOR PLA	IN & TAPPED HOLES	
UP TO 500 Ø1.0 OVER 500 Ø2.0		
		പംപം
	domr	
	37 hunta	ЭЦ.
Parker Hannifin M	U	
domnick hunter Filtration & Separation Division		
Dukesway, Team Valley Gateshead, Tyne & Wear		
England, NE11 0PZ TEL +44 (0)191 402 9000		
FAX +44 (0)191 482 6296		
www.parker THIS DOCUMENT IS COPYRIGH		
PARKER HANNIFIN LTD. IT MUS	T NOT BE COPIED IN	
WHOLE OR PART, USED FOR M. OTHERWISE DISCLOSED WITH	OUT PRIOR	016 A3
WRITTEN CONSENT OF THE CC		HEET
101-10518		/1

Model No. 101-10518.iam